

TOSHIBA

Leading Innovation >>>

e-STUDIO2518A

- > Black & White Multifunction Printer
- > 25 pages per minute
- > Medium to Large Workgroup
- > Copy, Print, Scan, Fax
- > Advanced Security
- > Customizable Touch Screen with Apps




steelhead
business products

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Colour WVGA Touch Screen Tilting Display
Copy Speed	25 Pages Per Minute (LT)
First Copy Out	Colour: 4.3 seconds
Warm-Up Time	Approximately 20 Seconds
Copy Resolution	2400 x 600 dpi with smoothing
Stack Feed Bypass	3.9" x 5.8" to 11 x 17", Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSD/ or 100-Sheet RADF
Scan Speed & Weights	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond Ledger (11x17")
Max. Original Size	Drawer 1: 550 Sheets-ST-R to Ledger
Paper Feed Sizes	Drawer 2: 550 Sheets-ST-R to Ledger Stack Feed Bypass: 100 Sheets-3.9x5.8" to 12x18", 12x47" Banners Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12x18" Opt. 550-Sheet Drawer for PFP-ST-R to 12x18" Opt. Envelope Cassette for PFP-App. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only
Paper Weights	Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-140 lb Index Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550 Sheets Drawer for PFP-16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17 lb-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Duplex	Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 100K
Weight	Approximately 125.2 lbs
Approx. Dimensions	23" (W) x 23" (D) x 31" (H)
Toner Yield	43,900 @ 5%
Power Source	120 Volts, 50/60 Hz, 12 Amps
Power Consumption	Maximum 1.5kW (120V)
CPU	Intel Atom™ 1.33 GHz (Dual-Core)
Memory	4GB
Hard Disk Drive	320GB Self-Encrypting Drive FIPS 140-2 Validated (Opt)

Security Features	User/Card/NFC Authentication, On-Board Data Scramble, SCEP, Disable e-File, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port & Role-Base Access Control, SMB Packet Sign, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG) IPsec (IKEv1, IKEv2, Secure Mode Change, CC Cert (ISO/IEC15408)* IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy/Lock/Expiration, Self Test, Job Access Control, Access Control for Job Log, PDF, Security Stamp, Digital Sig for Firmware Update, Integrity Check, Image Log
Environmental Stds. Certification	*Conformance with HCD-PPV1.0 in High Security Mode. Energy Star (V2.0), EPEAT Gold, Calif. Proposition 65, Canadian ECP, RoHS WHQL® (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP, AirPrint, Mopria

Scan Specifications

Scan Speed	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, Slim PDF
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
DSD/	MR4000	IPsec Enabler	GP1080
RADF	MR3031	Unicode Font Enabler	GS1007
Platen Cover	KA5005PC	Monotype Font Option	GB2050
		FIPS HDD Option	GE1230
Additional Paper Options		USB Hub	GR1310
Paper Feed Pedestal	KD1058	Embedded OCR Enabler	
Drawer Module	MY1048	Per Seat License	GS1080
Envelope Cassette Option	MY1049	Multi-Station Print Enabler	
Large Capacity Feeder	KD1059LT	Per Seat License	GS1090
Finishing Options		SharePoint Connector	GB1440
Inner Finisher	MJ1042	Exchange Connector	GB1450
50-Sheet Staple Finisher	MJ1109	Google Docs Connector	GB1540
Saddle-Stitch Finisher	MJ1110		
Hole Punch Unit for MJ1042	MJ6011	Miscellaneous Options	
Hole Punch Unit for MJ1109/MJ1110	MJ6105	Stand	STAND5005
Bridge Kit	KN5005	Accessible Arm	KK2550
Job Separator	MJ5015	Work Tray	KK5005
		Harness Kit for Coin Controller	GQ1280
		Manual Pocket	KK5008
Connectivity/Security Options			
FAX Unit/2nd Line for FAX Unit	GD1370N		
Wireless LAN/Bluetooth	GN4020		
Bluetooth Keyboard	GR9000		
Accessory Tray	GR1330		
Panel 10-Key Option	GR1340		
Card Reader Holder	GR1320		
Meta Scan Enabler	GS1010		

e-BRIDGE Next Print Specifications

Print Driver Languages	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	25 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (1 bit); 2,400 x 600 dpi with smoothing; 1200 x 1200 dpi (2 bit) or 3,600 x 1,200 dpi (with Smoothing) using PostScript 3
Operating Systems	Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Linux®, Unix®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX for Novell® Environments, EtherTalk® for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk PAP, EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit), Windows® Server 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32&64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit) Mac OS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, Toshiba e-Bridge Print & Capture App on IOS and Android (Available via Apple App Store or Google Play)
Device Management	TopAccess, EFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Designs and specifications subject to change without notice. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact Steelhead for availability. Toner yields are estimates based on 5% coverage using letter-size paper. Driver and connectivity features and support may vary based on the clients network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1.

Steelhead Business Products Ltd

address: 5589 Regent Street
Burnaby, BC V5B 4R6
sales: 604.473.9100
service: 604.473.9655
fax: 604.473.9699
web site: www.steelhead.net